

CO-Series CO₂ Lasers

The TELESIS CO-Series Laser Markers, available with standard power levels at 60W and 10W and are excellent choices for high duty cycle applications on plastic, rubber, wood,

paper, anodized metal and label marking applications. They are perfect for

"Marking-on-the Fly" as well as stationary marking. Their

RF-excited CO₂ tube assures a long life cycle

as well with virtually maintenance-

free operation. Due to their compact size and modular construction, the

CO-Series markers can go almost any place they are needed on the plant floor.











Model C10 Controller

LASER MARKER SPECIFICATIONS

Compliance	CDRH, CE
	10.6um
Laser Type	CO ₂
	Up to 10W
	Up to 60W
Head Weight	19.1kg (42.0lbs.)(10W)
	30.0kg (66lbs.)(60W)
Controller Weight	8.0 kg (18.0lbs.)
	85.7(L) x 16.5(W) x 22.1cm(H)
	(33.7" x 6.5" x 8.7")
CO60	97.1(L) x 21.0(W) x 22.1cm(H)
	(38.2" x 8.3" x 8.7")
Controller Dimensions	42.5(W) x 14.0(H) x 50.4cm(D)
	(16.7" x 5.5" x 19.9")
Input Power	100 - 240 VAC, 50 - 60 Hz
Maximum Power Consumption	on CO10A Less than 480W
Maximum Power Consumption	on CO60 Less than 1000W
Cooling	Air Cooled, Fan/Filter
	(no water cooling required)
Operating Temperature Range	15° to 30°C (59° to 86°F)
Humidity	10% to 90% Non-condensing

STANDARD LENS CONFIGURATIONS

FOCAL LENGTH	MARKING FIELD
75mm	50mm X 50mm (1.97" X 1.97")
100mm	70mm X 70mm (2.76" X 2.76")
150mm	100mm X 100mm (3.94" X 3.94")
200mm	140mm X 140mm (5.51" X 5.51")
	Other lens configurations are available

MARKING SPEED*

- · Up to 152m/minute (500ft./minute) line speed for "Mark-on-the-fly" applications
- 1300 characters/second
- *Character marking speeds and production line speeds depend on material, character size and the desired marking quality.

SOFTWARE

Software	MERLIN® II LS
Operating System	Windows® 2000, Windows XP,
Windows V	/ista™, Windows® 7, or Windows® 8
with Optional Er	mbedded, Desktop or Rackmount PC
Communication Interface	Serial TCP/IP I/O



