

Corporate Headquarters

28181 River Drive
Circleville, Ohio 43113
Phone: 740.477.5000
Sales: 800.654.5696
Fax: 740.477.5001

<http://www.telesis.com>
<http://www.pinstamp.com>

Worldwide Locations**TELESIS FRANCE** ■**TELESIS UNITED KINGDOM** ■**TELESIS NETHERLANDS** ■**TELESIS GERMANY** ■**TELESIS CHINA** ■

ProStation “COMPLETE SOLUTION” CLASS 1 LASER WORKSTATIONS FOR FQ10, FQ20, EV15 AND EV25

TELESIS NOW OFFERS
COMPLETE SELF-CONTAINED
CLASS 1 WORK STATION
PACKAGES FOR THE FQ10,
FQ20, EV15 AND EV25.

INCLUDES:

- **CLASS 1 LASER
ENCLOSURE FEATURING**

- Attractive, rugged fabricated sheet metal design
- Transverse laser head mounting for convenient loading and unloading
- Extruded aluminum floor for convenient attachment of work piece fixturing and parts handling accessories
- Work lamp and door interlock
- Keyboard and monitor arm

- **HEAVY DUTY MANUALLY ADJUSTED LASER HEAD MOUNTING POST**

or

- **PROGRAMMABLE Z-AXIS LASER HEAD MOUNTING POST
WITH 2-AXIS STEPPER CONTROLLER**

- **TOWER COMPUTER WITH 17” FLAT PANEL MONITOR,
KEYBOARD AND MOUSE**



For Optional Caster-Mounted Base, See Photo on Page 2



PINSTAMP® IdentiPlate®
BenchMark® TeleScribe®
Merlin® and MicroPin™
are trademarks of
Telesis Technologies, Inc.

© Copyright 2010
Telesis Technologies, Inc.
All rights reserved.

Specifications subject to
change without notice.

Also available with numerous optional workstation accessories including Fume Extraction System (P/N 60809 110VAC, PN 60810 240 VAC) and Caster-Mounted Base housing the PC, controller, and any other system peripherals (P/N 71145).

For standard workstations, specify part numbers as follows:

ProStation FQ10 (with manual head mounting post):	P/N 71196-x* (110VAC/60 Hz) P/N 71198-x* (220VAC/50 Hz)
ProStation FQ10Z (with programmable Z-axis):	P/N 71195-x* (110VAC/60 Hz) P/N 71197-x* (220VAC/50 Hz)
ProStation FQ20 (with manual head mounting post):	P/N 71220-x* (110VAC/60 Hz) P/N 71202-x* (220VAC/50 Hz)
ProStation FQ20Z (with programmable Z-axis):	P/N 71199-x* (110VAC/60 Hz) P/N 71201-x* (220VAC/50 Hz)
ProStation EV15 (with manual head mounting post):	P/N 71133-x** (110VAC/60 Hz) P/N 71190-x** (220VAC/50 Hz)
ProStation EV15Z (with programmable Z-axis):	P/N 71132-x** (110VAC/60 Hz) P/N 71189-x** (220VAC/50 Hz)
ProStation EV25 (with manual head mounting post):	P/N 71192-x** (110VAC/60 Hz) P/N 71194-x** (220VAC/50 Hz)
ProStation EV25Z (with programmable Z-axis):	P/N 71191-x** (110VAC/60 Hz) P/N 71193-x** (220VAC/50 Hz)

*For the FQ10, FQ10Z, FQ20 and FQ20Z

- x=1 for 100mm lens
- x=2 for 160mm lens
- x=3 for 163mm lens
- x=4 for 254mm lens
- x=5 for 330mm lens
- x=6 for 420mm lens
- x=7 for 350mm lens

**For the EV15, EV15Z, EV25 and EV25Z

- x=1 for 100mm lens
- x=2 for 160mm lens
- x=3 for 254mm lens
- x=4 for 330mm lens
- x=5 for 420mm lens



Shown with Optional Caster-Mounted Base

