

Near Edge Resin
NET Resin IQ

NET Resin IQ

High durability for near-edge labeling and coding

NET Resin IQ's full resin formulation offers excellent high-speed print capabilities of 12 IPS in near-edge applications. NET Resin IQ produces dark, black barcodes and images with superior print quality and durability in the most extreme labeling and coding applications.

**CleanStart feature is available on some tag and label ribbon configurations.*

Benefits

- High-speed print capability up to 12 IPS, ideal for flexible packaging
- Good smudge and scratch resistance
- Broad stock latitude on common flexible packaging substrates
- Superior heat resistance
- Dark black barcodes and images with solid fill and no show-through

Recommended Stocks

- Polyethylene
- Polypropylene
- PET
- Nylon Film

IIMAK Thermal Transfer Ribbons

NET MARK IQ	NET FLEX	NET RESIN IQ
		<p>Near Edge Resin High durability to endure abrasion in demanding applications.</p>
<p>Wax Ribbons for General Purpose Labeling GP725 High Mark</p>		
<p>Wax/Resin Ribbons for High Durability PM308 Prime Mark</p>		
<p>Resin Ribbons for Maximum Durability SP330</p>		
<p>Color Thermal Transfer Ribbons DC100 DC200 DC400 NET Color</p>		
<p>Security Enhanced Thermal Transfer Ribbons UV Invisible</p>		



310 Commerce Drive • Amherst, NY 14228
Toll-Free: 888.464.4625 • Phone: 716.691.6333
salesinfo@iimak.com • www.iimak.com

Applications



Snack



Dairy



Produce



Medical



Pharmaceutical



Health/Beauty



Life Sciences



Automotive



Outdoor

NET Resin IQ

Near Edge Resin

Outstanding stock latitude with above average print quality and chemical resistance. NET Resin IQ delivers superior heat resistance and is designed for near edge printers including TEC, Novexx, Avery, and flexible packaging coders Markem® and Videojet®.



Imaging Characteristics

Printer	Print Speed	Energy Range
Near-Edge	12 IPS	Low - Mid

Image Darkness	Scratch/Smudge	Chemical
>1.6 RD (densitometer)	Upper Resistance	Highest Resistance

Technical Specifications

Color Code Tab	Gold
Film Thickness	4.5 Microns
Total Ribbon Thickness	6.5 Microns
Transmission Density	1.50 MacBeth Scale
Ink Melting Point	70°C/158°F

Typical Compliance

- REACH – SVHC Free
- RoHS/WEEE
- TSCA
- CONEG
- California Proposition 65
- FDA GRAS Recognized
- FDA 21CFR175 for Indirect Food Contact
- ISEGA Approval Pending
- MSDS available at www.iimak.com
- Additional Regulatory Requirements Upon Request


Industry Leading Customer Service

- Free Clean Start® built-in printhead cleaner
- Free samples
- Free technical support 888.372.0137
- Free 24-hour print tests
- Over 500 SKUs stocked for same-day shipping
- Complete line of over 2,500 SKUs



DARTRONICS, INC.

PACKAGING AUTOMATION SPECIALISTS



150 WILLIAM ST. PERTH AMBOY, NJ 08861 / TOLL FREE: 800-298-8936 / PHONE: 732-324-0800 / FAX: 732-324-4488

WWW.DARTRONICS.COM

YOUTUBE / DARTRONICS

THE SINGLE SOURCE FOR YOUR

END-OF-LINE

PACKAGING, MARKING AND CODING NEEDS

310 Commerce Drive • Amherst, NY 14228
Toll-Free: 888.464.4625 • Phone: 716.691.6333
salesinfo@iimak.com • www.iimak.com
Thermal Transfer Ribbons made in the USA