

# PLS410 Automated Labeling

**PARAGON LABELING**  
Continuing the Legacy



Picture shows optional upgrade to Print and Apply

At Paragon Labeling Systems, we are committed to providing the most cost effective label application solutions available. Our PLS400 series of labeling systems present a modular and flexible design that allows you to reconfigure your labeling system as your needs evolve without needing to buy a whole new system. The PLS410 system is a feature rich system that can start as a preprinted label applicator system used for applying preprinted, decorative labels to products, cartons, cases, pallets, and totes. When you need to add printing capability for variable data or barcodes, the system can be easily and inexpensively upgraded to print and apply. With a full line of field interchangeable application modules, the PLS410 can label in virtually any orientation.

With its plate aluminum chassis, PLC controller and remote mount interface, this robust system delivers an unparalleled value proposition with many standard features that are only options on other systems. The peel-tip label gap sensor coupled with a highly accurate stepper drive ensures precise label placement every time. With more standard features than similar products, the PLS410 provides customers with the knowledge that their labeling needs are being met today and into the future



**SPEEDY**



**ACCURATE**



**DURABLE**

See reverse  
for product specifications.



**DARTRONICS, INC.**  
PACKAGING AUTOMATION SPECIALISTS



150 WILLIAM ST. PERTH AMBOY, NJ 08861 / TOLL FREE: 800-298-8936 / PHONE: 732-324-0800 / FAX: 732-324-4488

WWW.DARTRONICS.COM

YOUTUBE / DARTRONICS

THE SINGLE SOURCE FOR YOUR

**END-OF-LINE**

PACKAGING, MARKING AND CODING NEEDS

## TECHNICAL SPECIFICATIONS

- PLC Controlled
- Remote mount interface
- 4-Line, Backlit Interface with tactile keys
- Stepper motor label drive system
- Operator selectable label dispense speed (up to 24"/second)
- Peel-Tip label sensing
- "Teach" label gap sensor
- Accurate to +/- 1/64"
- Plate aluminum construction
- Fully enclosed chassis
- Pressurized cabinet

## LABEL SPECIFICATIONS

	Min	Max
Label Width	.5" (12.7mm)	7.1" (180 mm)
Label Length	.5" (12.7mm)	18" (457.2mm)
Roll Size	3" ID	12" OD

## AIR REQUIREMENTS

- 30-80 PSI (application dependant)
- Clean, dry, non-oiled
- Air not required for wipe (merge) label applications

## POWER

115 VAC, 6 Amp

## DIMENSIONS

- 24" (610 mm) wide x 22" (610 mm) tall x 15" (381 mm) deep
- Applicator module not included above

## Weight

80lbs



Picture shows optional upgrade to Print and Apply

## OPERATING ENVIRONMENT

	Min	Max
Temp	30°	110°
Humidity (non-condensing)	10%	95%

## APPLICATOR MODULES

- Wipe (merge)
- Tamp
- Dual Panel Tamp
- Corner Wrap
- Blow
- Tamp-Blow
- Smart-Tamp
- Pneumatic Roll-On

## ADDITIONAL OPTIONS

- Upgrade to Print & Apply
- Mounting stand (many to choose from)
- Product detection sensors (many to choose from)
- 3-Color warning beacon
- Dual label application sensing
- Basic product handling